

(19)



JAPANESE PATENT OFFICE

BEST AVAILABLE COPY

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **09312741 A**(43) Date of publication of application: **02.12.97**

(51) Int. Cl.

H04N 1/19**H04N 1/04****H04N 1/401****H04N 5/335**(21) Application number: **08125748**(71) Applicant: **TOSHIBA CORP**(22) Date of filing: **21.05.96**(72) Inventor: **MAKINO TOMONORI**(54) **IMAGE INPUT DEVICE**

COPYRIGHT: (C)1997,JPO

(57) Abstract:

PROBLEM TO BE SOLVED: To compensate a signal even in the case of using a strong light source by controlling drive of a photoelectric conversion means thereby changing the exposure period of the photoelectric conversion means.

SOLUTION: In the case of conducting signal compensation, a drive timing of a CCD by the special scan system is switched. A shift pulse signal S21 is made up of a pulse where two periods of a scan A with the same scanning period as the usual scanning and a scan B with a shorter scan period are repeated. Furthermore, a frequency of a clock signal S22 is changed depending on the scan so that the same number of pulse signals is generated between the two periods of scan A and scan B. An output A corresponding to the scan A of a CCD output S23 reaches a saturated point similarly to the case with the usual scan, but the output B corresponding to the scan B does not reach the saturated point. Then the signal is compensated by sampling the output B at that time.

